

Parallelomatic

Parallelomatic, parallelometer especially designed for the surveying. The peculiar features of the articulated pantograph, **easy to handle and sensitive, allow maintaining the chuck axis perfectly parallel all over the very wide working plane.** The conical insertion mandrel, which makes easier the fitting and the replacing of all analysis accessories, can be provided with a vertical return (MM, optional). The accessories holder is pre-arranged for the application of a halogen spotlight (LA, optional). The parallelometer can be equipped with a feeder (STP, accessory not included) **that includes an electronic regulator for the feeding of thermal probes, used for wax smoothing.**

Quality details

- Ideal for the surveying
- Tri-dimensional pantograph arm
- Quick accessories holder mandrel sliding on bearing brass
- Quick model holder A21
- Available in two versions with or without feeder for thermal probes, used for wax smoothing



Assembled STP feeder



Included accessories

- Quick model holder A21 with extension PRO1
- Analytic point
- Graphite holder
- Calibrators 0,25 – 0,50 – 0,75 mm
- Wax knife
- Reducing chuck for the insertion of accessories with cylindrical shank \varnothing 2,35 mm

Performances

- Surveying

Technical data

Dimensions (mm)	200x240 (+135 with STP) x 630
Weight (kg)	4,5 (+0,75 with STP)
Vertical range H max/h min/stroke (mm)	170/95/55